

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	110	116		
	kW	88	93		
Prime Power (PRP)	kVA	101	106		
	kW	81	85		



Engine					
Manufacturer		VOLVO			
Origin		SWEDEN			
Model		TAD531GE			
No of Cylinder / Configuration		4 - INLINE			
Displacement		lt	4,76		
Bore / Stroke		mm	108 / 130		
Compression Ratio		18:1			
Aspiration		Turbocharged and Intercooled			
Governor Type		HEINZMANN EDC4			
Cooling System		WATER			
Coolant Capacity		lt	12,5		
Lubrication Oil Capacity		lt	11		
Electrical System		VDC	12		
Speed / Frequency			1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power		kWm	102	111	
Fuel Consumption	g/kWh	110 %	219	218	
		100 %	217	219	
		75 %	221	226	
		50 %	244	259	
Exhaust Outlet Temperature		°C	557	516	
Exhaust Gas Flow		m³/min	18,4	22,1	
Combustion Air Flow		m³/min	6,089	7,75	
Cooling Air Flow		m³/min	78	90	



Standby Power



Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator					
Manufacturer		MARELLI			
Origin		ITALY			
Model		MJB225MA4			
No of Phase		3			
Power Factor		0,8			
No of Bearing		SINGLE			
No of Poles		4			
No of Leads		12			
Voltage Regulation (Steady State)		± %0,5			
Insulation Class		H			
Degree of Protection		IP 23			
Excitation System		AVR (Automatic Voltage Regulator), Brushless			
Connection Type		STAR			
Total Harmonic Content (No Load)		< %2			
Frequency		Hz	50	60	
Voltage Output		VAC	230 / 400	254 / 440	
Rated Power (Standby)		kVA	115	139	
Efficiency		%	91,8	91,9	

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	1037 x 3265 x 1700	1707	168	TBA
Open Skid	750 x 2400 x 1470	1239	144	TBA



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask TBD: To Be Determined NA: Not Available N/A: Not Applicable TTD110VV0508-EN